

# SHREDDERS

**“Waste management equipment for the demanding maritime and offshore industry that gets the job done efficiently, safely and in an environmentally responsible manner.”**



**DT-230SR, DT-575SR,  
DT-1575SR & DT-190LCS**

## KEY BENEFITS

- Stainless steel units for indoor or outdoor placement
- Wheeled, interchangeable stainless steel containers for easy waste segregation and logistics.
- Delitek products are certified by DNV.
- Powerful electric motors for high shaft torque.
- Shredding directly into big bags for easy and safe deployment of waste. (HD plastic bags as alternative for DT-230SR).
- Easy installation and operation (Plug & Play).

**MARINE****OFFSHORE****NAVY****CRUISE****YACHT****FISHING****ONSHORE****DT-230SR**

|                          |   |
|--------------------------|---|
| Material                 | Stainless steel AISI 304, AISI 316 or painted steel |
| Capacity                 | 0,2 m <sup>3</sup>                                  |
| Loading opening (W x H)  | 600mm x 350mm                                       |
| Dimensions (W x D x H)   | 940mm x 1348mm x 1936mm                             |
| Weight (Incl. container) | 470 Kg  |
| Motor voltage            | 380~440V, 3Ph, 50~60Hz                              |
| Motor power              | 3 kW  |
| Blade size               | 2mm x 8mm   |
| Shaft torque             | 1900 Nm   |
| Noise level              | <70dB Max   |

**DT-575SR**

|                          |                                      |
|--------------------------|--------------------------------------|
| Material                 | Stainless steel AISI 304 or AISI 316 |
| Capacity                 | 0,5 m <sup>3</sup>                   |
| Loading opening (W x H)  | 695mm x 547mm                        |
| Dimensions (W x D x H)   | 1040mm x 1786mm x 2605mm             |
| Weight (Incl. container) | 1260 Kg                              |
| Motor voltage            | 380~440V, 3Ph, 50~60Hz               |
| Motor power              | 7,5 kW                               |
| Blade size               | 2mm x 12mm                           |
| Shaft torque             | 4580 Nm                              |
| Noise level              | <70dB Max                            |

**DT-1575SR**

|                          |                                      |
|--------------------------|--------------------------------------|
| Material                 | Stainless steel AISI 304 or AISI 316 |
| Capacity                 | 1,5 m <sup>3</sup>                   |
| Loading opening (W x H)  | 695mm x 547mm                        |
| Dimensions (W x D x H)   | 1480mm x 1786mm x 2880mm             |
| Weight (Incl. container) | 1280 Kg                              |
| Motor voltage            | 380~440V, 3Ph, 50~60Hz               |
| Motor power              | 7,5 kW                               |
| Blade size               | 2mm x 12mm                           |
| Shaft torque             | 4580 Nm                              |
| Noise level              | <70dB Max                            |

**DT-190LCS**

|                          |  |
|--------------------------|--|
| Material                 | Stainless steel AISI 304 or AISI 316 - PVC Container |
| Capacity                 | 190 Litre  |
| Loading opening (W x H)  | 600mm x 350mm  |
| Dimensions (W x D x H)   | 940mm x 1348mm x 2041mm                              |
| Weight (Incl. container) | 440 Kg   |
| Motor voltage            | 380~440V, 3Ph, 50~60Hz                               |
| Motor power              | 3 kW   |
| Blade size               | 2mm x 8mm  |
| Shaft torque             | 1900 Nm  |
| Noise level              | <70dB Max  |

**Delitek AS (Head Office)**

Moloveien 1 N-8432 Alsvåg, Norway Tel: +47 76 18 57 60 Fax: +47 76 13 42 77 e-mail: mail@delitek.no  
[www.delitek.no](http://www.delitek.no)